



HIGH PRESSURE CHECK VALVES CH SERIES

8250 Boyle Parkway Twinsburg, Ohio U.S.A. 44087 mySSP.com 1.330.425.4250



CH SERIES POPPET CHECK VALVES

Working Pressure: up to 6000 psi (413 bar)

Temperature Range: -40 to 400°F (-40 to 204°C)

End Connections:

Types: Tube fitting, NPT and ISO pipe

Sizes: 1/8" through 1" and 6, 8, 10 and 12mm

Standard Material: 316 SS with Fluorocarbon FKM O-ring.

Other materials are available.

Cracking pressures: 1/3, 1, 5, 10 and 25 psi (0.2 to 1.7 bar)

100% factory tested:

Seat / Shell to 1000 psig with nitrogen

Cracking and resealing pressure verification


Pressures / temperatures & flow

SERIES	MAXIMUM FLOW COEFFICIENT (CV)	NOMINAL CRACKING PRESSURE PSI (BAR)	DOWNSTREAM PRESSURE AT 70°F (20°C) PSIG (BAR)
CH4	0.60	1/3, 1, 5, 10 and 25 (0.03, 0.07, 0.69 and 1.8)	6000 (413 bar)
CH8	2.15		5000 (345 bar)
CH16	3.25		

Cracking & Reseal Pressures

Nominal Cracking Pressure psig (bar)	Cracking Pressure Range psig (bar)	Reseal Pressure psig (bar)
1/3 (0.03)	Up to 3 (0.21)	Up to 6 (0.42) back pressure
1 (0.07)	Up to 4 (0.28)	Up to 5 (0.35) back pressure
5 (0.35)	3 TO 9 (0.21 TO 0.63)	Up to 2 (0.14) back pressure
10 (0.69)	7 TO 15 (0.49 TO 1.1)	3 (0.21) or more upstream pressure
25 (1.8)	20 TO 30 (1.4 TO 2.1)	17 (1.2) or more upstream pressure

Materials of Construction




ID	Component	Material
1*	Inlet Body	316 SS
2*	Poppet	316 SS
3*	Spring	302 SS
4*	O-ring	Fluorocarbon FKM
5*	O-ring Retainer	316 SS
6*	Connector Gasket	316 SS
7*	Outlet Body	316 SS

*Wetted components

Part Numbers and Dimensions

End Connections		Basic Part Number	Dimensions		
Type	Size		Valve Size	A in. (mm)	H (HEX) in. (mm)
Fractional Tube Fitting	1/8	CH4-D2	CH4	2.27 (57.7)	11/16
	1/4	CH4-D4	CH4	2.44 (62.0)	11/16
	3/8	CH8-D6	CH8	2.75 (69.9)	1
	1/2	CH8-D8	CH8	2.96 (75.2)	1
	3/4	CH16-D12	CH16	3.53 (89.7)	1 3/4
	1	CH16-D16	CH16	3.88 (98.6)	1 3/4
Metric Tube Fitting	6	CH4-DM6	CH4	2.44 (62.0)	11/16
	8	CH8-DM8	CH8	2.70 (68.6)	1
	10	CH8-DM10	CH8	2.75 (69.9)	1
	12	CH8-DM12	CH8	2.96 (75.2)	1
Female NPT	1/4	CH4-4PF	CH4	2.26 (57.4)	11/16
	3/8	CH8-6PF	CH8	2.55 (67.8)	1
	1/2	CH8-8PF	CH8	3.03 (77.0)	1 1/16
	3/4	CH16-12PF	CH16	3.23 (82.0)	1 3/4
	1	CH16-16PF	CH16	3.83 (97.3)	1 3/4
Female ISO Tapered	1/4	CH4-4FRT	CH4	2.38 (60.5)	11/16
	3/8	CH8-6FRT	CH8	2.86 (72.6)	1
	1/2	CH8-8FRT	CH8	3.29 (83.6)	1 1/16
Male NPT	1/8	CH4-2PM	CH4	1.9 (48.3)	11/16
	1/4	CH4-4PM	CH4	2.17 (55.1)	11/16
	3/8	CH8-6PM	CH8	2.36 (59.9)	1
	1/2	CH8-8PM	CH8	2.73 (69.3)	1
	3/4	CH16-12PM	CH16	3.23 (82.0)	1 3/4
	1	CH16-16PM	CH16	3.67 (93.2)	1 3/4
Male ISO Tapered	1/4	CH4-4MRT	CH4	2.17 (55.1)	11/16
	1/2	CH8-8MRT	CH8	2.73 (69.3)	1
Male NPT to Female NPT	1/4	CH4-4PM4PF	CH4	2.26 (57.4)	11/16
	1/2	CH8-8PM8PF	CH8	2.89 (73.4)	1 1/16
Fractional Tube to Male NPT	3/8	CH8-D66PM	CH8	2.56 (65.0)	1
	1/2	CH8-D88PM	CH8	2.74 (69.6)	1





PART NUMBER CONFIGURATION



Cracking Pressure

Cracking Pressure psig	Designator
1/3	1/3
1	1
5	5
10	10
25	25

MATERIAL DESIGNATOR: Stainless Steel- 316

Example: CH4-D4-1-316

O-RINGS

Fluorocarbon FKM O-rings are the standard seal material on CH check valves. To order, non-standard O-rings insert the designator from the table below into the valve part number. Example: CH4-D4-316-BN

MATERIAL	DESIGNATOR	TEMPERATURE RATING °F (°C)
Fluorocarbon FKM	Blank	-10 TO 400 (-23 to 204)
NITRILE	-BN	-20 TO 250 (-28 TO 121)
LOW-TEMP NITRILE	-NBR3	-40 TO 250 (-40 TO 121)
ETHYLENE PROPYLENE	-EP	-50 TO 250 (-45 TO 121)
KALREZ	-KZ	0 TO 400 (-17 TO 204)

PRODUCTION TESTING

Check valves are 100% factory tested with nitrogen after assembly to confirm spring cracking pressure, and for seat shell leakage at 1000 psi.

Please consider total system design considerations when selecting products to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

Duolok®, Unilok®, Griplok®, & TruFit® are registered trademarks of SSP.

Visit www.mySSP.com for the controlled version of data.